

VF Vacuum Fittings



OUR PEOPLE MAKE THE DIFFERENCE

Features

特点

- ③ Stainless steel construction, fluorocarbon FKM O-ring.
不锈钢结构，碳氟化合物 FKM O 形圈。
- ③ Available in tube sizes from 1/16" to 1 1/2".
可用于 1/16 至 1 1/2 in. 尺寸的卡套管。
- ③ Temperature rating: -25 to 400°F (-31 to 204°C).
温度范围: -31°C 至 204°C (25°F 至 400°F)。
- ③ Knurled nut for easy, finger-tight assembly.
滚花螺母便于手紧装配。
- ③ Reliable, repeatable sealing performance.
可靠、可重复的密封性能。

Testing

测试

- ③ The VF vacuum fitting design has been helium leak tested to a maximum leak rate of 4×10^{-9} std cm³/s at ambient temperature.
VF 系列真空管接头设计经过氦气泄漏测试，室温下的最大泄漏率为 4×10^{-9} std cm³/s。
- ③ The leak rate increases as temperature increases due to permeation through the O-ring.
由于通过 O 形圈的渗透，泄漏率随温度的升高而增大。

Cleaning and Packaging

清洁和包装

- ③ VF vacuum fittings meet the requirements of MAGNOX Standard Cleaning and Packing.
VF 系列真空管接头遵循《MAGNOX 标准清洁和包装规范》。
- ③ VF vacuum fittings are cleaned to remove machine oil, grease and loose particles.
VF 系列真空管接头经过清洁，去除了机油、油脂和自由颗粒。

Ordering Information


订购信息

- ③ The E dimension refers to the smallest nominal inside diameter of the part.
尺寸 E 代表零件最小公称内径值。
- ③ To order straight fittings bored through, add -T to the ordering number.
Example: VF-U-4-T
预订购内孔直通接头，请在订购号中附加 T。
示例: VF-U-4-T
- ③ For pre-ordering full fluorine ether material sealing rings, please append "FF" in the order number.
Example: VF-U-4-FF
预订购全氟醚材质密封圈，请在订购号中附加 FF
示例: VF-U-4-FF

Dimensions 尺寸


⊙ Dimensions are for reference only and are subject to change.
尺寸仅供参考，如有变更，恕不另行通知。

Unions 联合接头




T-Tube O.D. (in.)	Ordering Number	Dimensions, mm			
		L	C	E	G
1/16	VF-U-1	31.2	10.9	1.3	3/8
1/8	VF-U-2	35.6	10.9	2.3	9/16
1/4	VF-U-4	41.4	15.7	4.6	11/16
3/8	VF-U-6	46.0	16.8	7.1	13/16
1/2	VF-U-8	46.7	20.3	10.2	15/16
5/8	VF-U-10	46.7	21.3	12.7	1 1/8
3/4	VF-U-12	52.1	23.9	15.7	1 1/4
1	VF-U-16	54.6	23.9	22.1	1 9/16
1 1/2	VF-U-24	57.6	23.9	35.1	2 1/16

Reducing Unions 变径联合接头




T-Tube O.D. (in.)	Tx-Tube O.D. (in.)	Ordering Number	Dimensions, mm					
			L	C	Cx	E	G	Gx
3/8	1/4	VF-RU-6-4	43.7	16.8	15.7	4.6	13/16	11/16
1/2		VF-RU-8-4	44.4	20.3			15/16	

Tube Fitting Unions 卡套管联合接头




T-Tube O.D. (in.)	Tx-Tube O.D. (in.)	Ordering Number	Dimensions, mm				
			L	C	Cx	E	G
1/4	1/4	VF-TFU-U4-T4	42.2	15.7	15.2	4.6	11/16
3/8	3/8	VF-TFU-U6-T6	46.0	16.8	16.8	7.1	13/16
1/2	1/2	VF-TFU-U8-T8	49.5	20.3	22.9	10.2	15/16

Union Elbows 联合弯头




T-Tube O.D. (in.)	Ordering Number	Dimensions,mm			
		C	E	G	L
1/4	VF-UE-4	15.7	4.6	11/16	29.0
3/8	VF-UE-6	16.8	7.1	13/16	34.5
1/2	VF-UE-8	20.3	10.2	15/16	34.5

Union Tees 三接头




T-Tube O.D. (in.)	Ordering Number	Dimensions,mm				
		A	C	E	G	L
1/8	VF-UT-2	53.8	10.9	2.3	9/16	26.9
1/4	VF-UT-4	58.4	15.7	4.6	11/16	29.2
3/8	VF-UT-6	69.1	16.8	7.1	13/16	34.5
1/2	VF-UT-8	69.1	20.3	10.2	15/16	34.5
3/4	VF-UT-12	83.8	23.9	15.7	1 1/4	41.9
1	VF-UT-16	92.4	23.9	22.1	1 9/16	46.2

Male Connectors 阳螺纹接头




Tube O.D. (in.)	NPT size in.	Ordering Number	Dimensions, mm				
			L	B	C	E	G
1/16	1/8	VF-MC-U1-N2	28.4	9.6	10.9	1.3	3/8
1/8	1/8	VF-MC-U2-N2	31.0	9.6	10.9	2.3	9/16
1/4	1/8	VF-MC-U4-N2	34.3	9.6	15.7	4.6	11/16
	1/4	VF-MC-U4-N4	38.9	14.2			
3/8	1/8	VF-MC-U6-N2	36.6	9.6	16.8	4.6	13/16
	1/4	VF-MC-U6-N4	41.1	14.2		7.1	
1/2	3/8	VF-MC-U8-N6	41.9	14.2	20.3	10.2	15/16
	1/2	VF-MC-U8-N8	46.7	19.1			
3/4	3/4	VF-MC-U12-N12	49.8	19.1	23.9	15.7	1 1/4
1	1	VF-MC-U16-N16	57.2	23.9	23.9	22.1	1 9/16

Adapters 转换接头



T-Tube O.D. (in.)	Tx-Tube O.D. (in.)	Ordering Number	Dimensions, mm			
			L	C	E	G
1/16	1/4	VF-AM-U1-W2	28.4	10.9	1.3	3/8
1/8	1/4	VF-AM-U2-W2	30.5	10.9	2.3	9/16
	3/8	VF-AM-U2-W6	30.7			
1/4	1/4	VF-AM-U4-W4	34.0	15.7	4.6	11/16
	3/8	VF-AM-U4-W6	33.8			
	1/2	VF-AM-U4-W8	37.3			
3/8	3/8	VF-AM-U6-W6	37.3	16.8	7.1	13/16
	1/2	VF-AM-U6-W8	40.1			
1/2	5/8	VF-AM-U8-W10	41.7	20.3	10.2	15/16
	3/4	VF-AM-U8-W12	42.9			
3/4	1	VF-AM-U12-W16	45.2	23.9	15.7	1 1/4
1	1 1/4	VF-AM-U16-W20	45.7	23.9	22.1	1 9/16
1 1/2	1 1/2	VF-AM-U24-W24	50.3	23.9	31.8	2 1/16

Nuts 螺母



T-Tube O.D. (in.)	Ordering Number	Thread Size	Dimensions, mm		
			E	L	G
1/16	VF-N-1	1/4-20 UNC	1.8	9.6	3/8
1/8	VF-N-2	3/8-20 UN	3.3	10.4	9/16
1/4	VF-N-4	1/2-20 UNF	6.6	13.5	11/16
3/8	VF-N-6	5/8-20 UN	9.6	15.7	13/16
1/2	VF-N-8	3/4-20 UNEF	13.0	15.7	15/16
5/8	VF-N-10	15/16-20 UNEF	16.0	15.7	1 1/8
3/4	VF-N-12	1 1/16-20 UN	19.3	18.3	1 1/4
1	VF-N-16	1 3/8-20 UN	25.6	18.3	1 9/16
1 1/2	VF-N-24	1 7/8-20 UN	38.4	18.3	2 1/16

O-rings O-形圈



T-Tube O.D. (in.)	Ordering Number	Material
1/16	VF-OR-1	70 durometer fluorocarbon FKM
1/8	VF-OR-2	
1/4	VF-OR-4	
3/8	VF-OR-6	
1/2	VF-OR-8	
5/8	VF-OR-10	
3/4	VF-OR-12	
1	VF-OR-16	
1 1/2	VF-OR-24	

因我们而与众不同

OUR PEOPLE MAKE THE DIFFERENCE

www.magnox.com.cn

Suzhou Magnox Hygienic Materials Co., Ltd
No.10 Xihenggang Street, Yangchenghu Town,
Xiangcheng Area, Suzhou City.
Tel:+86-0512-65168151
E-mail:service@magnox.com.cn

我们的技术文件仅用于告知我们的客户。针对一些特定应用的测试条件获得的实验数据和结果，其有效性尚依赖于许多我们不可控的因素。因此，用户有责任根据自己特定需求仔细核实上述结果的有效性和产品的适用性。根据该目录中所列信息引起的争议将不予支持。技术参数如有更改，恕不另行通知。产品图片包含的某些附件可能不作为所印目录号的标准配件提供。